


BYM14-19-01RD

螺纹插装阀用电磁铁 Solenoid for threaded cartridge valve


DC 12V
DC 24V

其它规格可定做
Other can be customized

- 适用于 SD3E-B2 系列常开型电液螺纹插装阀
 - 螺纹连接，线圈可实现不停机更换
 - 配备手动调整装置
 - 线圈内孔 $\phi 19$ ，全塑料工艺
- Applicable to SD3E-B2 series normally open electro-hydraulic threaded cartridge valve
 - Threaded connection, coil can be replaced without stopping
 - Equipped with manual adjustment device
 - Coil inner hole $\phi 19$. All-plastic sealing process




外形及连接尺寸 Outline and connection dimensions



技术参数 /technical parameter		
环境温度 Ambient temperature	°C	-25~50
电压波动范围 Voltage fluctuation range	%	85~110
额定功率 Rated power	W	27
额定行程 Rated stroke	mm	1.6
全行程 Full stroke	mm	3.5
工作油压 Working oil pressure	Mpa	≤ 21
防护等级 Degree of protection		IP67
操作频率 Operating frequency	T/h	12000
通电持续率 Power on duration	%	100
绝缘等级 Insulation class		H(180)
电气连接方式 Electrical connection mode		DT04-2P

力 - 位移特性曲线 F-S characteristic curve



注意事项 matters needing attention

1. 线圈不得单独通电使用，有烧损风险！
 2. 非防爆线圈，不得使用在有爆炸危险的介质中！
 3. 线圈安装后，必须接地可靠，否则有触电危险！
1. The coil shall not be powered on alone, which has the risk of burning!
 2. Non explosion-proof coil shall not be used in medium with explosion risk!
 3. After the coil is installed, it must be grounded reliably, otherwise there is a risk of electric shock !

样本数据来源于试验室环境，仅供参考，贵公司如需最新数据或有特殊需求，欢迎联系博业液压工程师。
The sample data comes from the laboratory environment and is only for reference. If your company needs the latest data or has special needs, please contact Boye hydraulic engineer.